

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Contact Spray Adhesive**

Article number: 86593

1.2 Relevant identified uses of the substance or mixture and uses advised against

FOR PROFESSIONAL AND INDUSTRIAL USE ONLY

Application of the substance / the mixture Adhesive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KENT (United Kingdom) Ltd

Forsyth House

Pitreavie Drive

Pitreavie Business Park

Dunfermline

Fife

KY11 8US

Tel: +44 01383 723344 / 0800 136925 Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

Fax: +44 1383 620079

SDS@kenteurope.com

1.4 Emergency telephone number:

Tel: +44 01383 723344 During normal office hours - Monday - Thursday 8.30am - 5.30pm, Friday 9.00am - 3.00pm

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acetone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours/spray.
 P280 Wear protective gloves / eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of the substances listed below with harmless additions.

Dangerous components:

CAS: 115-10-6 EINECS: 204-065-8	Dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	50-75%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<5%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

In case of unconsciousness bring patient into stable side position for transport.
 Supply fresh air; consult doctor in case of symptoms.

After skin contact

Instantly remove any clothing soiled by the product.
 If skin irritation continues, consult a doctor.
 Instantly rinse with water.

After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.**After swallowing** In case of persistent symptoms consult doctor.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

· **Suitable extinguishing agents** CO₂, extinguishing powder or water haze. Fight larger fires with water haze or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.
 Wear self-contained breathing apparatus.
 Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

Collect contaminated fire fighting water separately. It must not enter drains.

(Contd. of page 2)

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on flames or red-hot objects.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:**

Store in cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:** Protect from heat and direct sunlight.**Storage class 2 B****7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Additional information about design of technical systems:** No further data; see item 7.**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**WEL Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm**Regulatory information** WEL: EH40/2020**DNELs****115-10-6 Dimethyl ether**Inhalative Long term systemic effect 1894 mg/m³ (Worker)**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Dermal Long term systemic effect 773 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 2035 mg/m³ (Worker)**67-64-1 Acetone**

Dermal Long term systemic effect 186 mg/kg bw/day (Worker)

Inhalative Long term systemic effect 1210 mg/m³ (Worker)Acute local effect 2420 mg/m³ (Worker)**8050-26-8 Resin acids and Rosin acids, esters with pentaerythritol**

Dermal Long term systemic effect 6.3 mg/kg/day (Worker)

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 3)

Inhalative	Long term systemic effect	44.6 mg/m³ (Worker)
6683-19-8 Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate)		
Dermal	Long term systemic effect	27 mg/kg/day (Worker)
Inhalative	Long term systemic effect	9.5 mg/m³ (Worker)
· PNECs		
115-10-6 Dimethyl ether		
PNEC	0.155 mg/l (Aqua (freshwater)) 1549 mg/l (Aqua (intermittent)) 0.016 mg/l (Aqua (marine water)) 0.681 mg/l (Freshwater sediment) 0.069 mg/l (Marine water sediment) 0.045 mg/l (Soil)	
67-64-1 Acetone		
PNEC	10.6 mg/l (Aqua (freshwater)) 21 mg/l (Aqua (intermittent)) 1.06 mg/l (Aqua (marine water)) 30.4 mg/kg (Freshwater sediment) 3.04 mg/kg (Marine water sediment) 29.5 mg/kg (Soil)	
8050-26-8 Resin acids and Rosin acids, esters with pentaerythritol		
PNEC	0.027 mg/l (Aqua (freshwater)) 0.27 mg/l (Aqua (intermittent)) 0.003 mg/l (Aqua (marine water)) 625.79 mg/kg (Freshwater sediment) 62.58 mg/kg (Marine water sediment) 2 mg/l (Sewage treatment plant) 125 mg/kg (Soil)	
6683-19-8 Pentaerythritol tetrakis (3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate)		
PNEC	0.04 mg/l (Aqua (freshwater)) 0.86 mg/l (Aqua (intermittent)) 0.004 mg/l (Aqua (marine water)) 4000000 mg/kg (Freshwater sediment) 4000000 mg/kg (Marine water sediment) 1 mg/ml (Sewage treatment plant) 798000 mg/kg (Soil)	

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and hygienic measures

Keep away from foodstuffs, beverages and food.
 Take off immediately all contaminated clothing
 Wash hands during breaks and at the end of the work.
 Avoid contact with the eyes and skin.

· Breathing equipment:

Only during spraying without adequate removal by suction.
 Filter AX / P (EN 14387)

· Protection of hands:



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Wear suitable gloves tested to EN 374

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 4)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level 6 > 480 minutes

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses (EN 166)

Tightly sealed safety glasses. (EN 166)

· **Body protection:** Protective work clothing (EN-13034/6)

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Colour:	Light yellow
Odour:	Solvent-like

· **Change in condition**

Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	55 °C (@ 1013 hPa)

Flash point:	Not applicable, as aerosol
--------------	----------------------------

Ignition temperature:	275 °C
-----------------------	--------

Self-inflammability:	Product is not selfigniting.
----------------------	------------------------------

Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
-----------------------	---

· **Critical values for explosion:**

Lower:	1.0 Vol %
Upper:	13 Vol %

Density	Not determined
---------	----------------

Relative density at 20 °C	0.68
---------------------------	------

· **Solubility in / Miscibility with**

Water:	Unsoluble
--------	-----------

· **Viscosity:**

dynamic at 20 °C:	~300 cps
kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	607 g/l VOC
-------------------	-------------

Solids content:	~ 30%
-----------------	-------

9.2 Other information	No further relevant information available.
-----------------------	--

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known

· **10.4 Conditions to avoid** Heat. Hot surfaces. Sources of ignition. Flames.

· **10.5 Incompatible materials:** Strong acids and oxidizing agents

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 5)

· **10.6 Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (Rat)
Dermal	LD50	>2920 mg/kg (RAB)
Inhalative	LC50 (4 hr)	>25.2 mg/l (Rat)

67-64-1 Acetone

Oral	LD50	5800 mg/kg (Rat)
Dermal	LD50	20000 mg/kg (Rabbit)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **Additional toxicological information:**

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **STOT-single exposure**

May cause drowsiness or dizziness.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· **Aquatic toxicity:**

115-10-6 Dimethyl ether

EC50 (48 hr)	>4000 mg/l (Daphnia magna)
EL50 (48 hr)	4001 mg/l (Daphnia magna)
LC50 (48 hr)	755549 mg/l (Daphnia magna)
LC50 (96 hr)	154.9 mg/l (Algae)
	4001 mg/l (Poecilia reticulata)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EL50 (48 hr)	3 mg/l (Daphnia magna)
EL50 (72 hr)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50	11.4 mg/l (Oncorhynchus mykiss) (96 hr)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
NOEC (21 days)	0.17 mg/l (Daphnia magna)
NOELR	3 mg/l (Pseudokirchneriella subcapitata) (72 hr)

67-64-1 Acetone

EC50	61150 mg/l (Activated sludge) (30 mins)
EC50 (48 hr)	39 mg/l (Daphnia magna)
LC50 (96 hr)	8300 mg/l (Fish)
	5540 mg/l (Oncorhynchus mykiss)
NOEC (28 days)	2212 mg/l (Daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 6)

Additional ecological information:**General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**· **Recommendation** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.**Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number**· **ADR, IMDG, IATA**

UN1950

14.2 UN proper shipping name· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT

· **IATA**

AEROSOLS, flammable

14.3 Transport hazard class(es)· **ADR**· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG**· **Class**

2.1

· **Label**

2.1

· **IATA**· **Class**

2.1

· **Label**

2.1

14.4 Packing group· **ADR, IMDG, IATA**

Void

14.5 Environmental hazards:

Product contains environmentally hazardous substances: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· **Marine pollutant:**

Symbol (fish and tree)

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 7)

· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Kemler Number:	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category** P3a FLAMMABLE AEROSOLS· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t· **National regulations**· **Technical instructions (air):**

Class	Share in %
NK	58.0

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2021

Version number 24

Revision: 07.04.2021

Trade name: Contact Spray Adhesive

(Contd. of page 8)

H411 Toxic to aquatic life with long lasting effects.

 · **Department issuing data specification sheet:** Environment protection department

 · **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

 · **Data compared to the previous version altered.** *

GB